Q FLOORS

Exquisite Flooring

Nordic Wood XQ-SPC-05

EXQUISITE RANGE

Our **Engineered Hybrid Flooring** is the newest flooring development in today's market. Created using the latest flooring technologies our Engineered Hybrid floors are versatile and durable having features to suit all residential and commercial spaces. We have expertly designed our boards wider and longer to make any area appear more spacious, whilst retaining a natural timber appearance.

Our Engineered Hybrid Floors will fill your space with a sophisticated and modern ambiance, with the endurance to last many years.

FEATURES

- Hard Wearing
- Waterproof
- Natural timber appearance
- Quiet and comfortable to walk on
- Easy to clean
- Pet Friendly
- Handles well against scratches and scuff marks
- Impact resistance
- Can be installed over uneven surfaces
- Dimensionally stable
- Fire retardant
- Anti-Bacterial Surface Properties
- Stain Resistant properties
- Slip Resistance Class: P4

PRODUCT DETAILS

Dimension: 1800mm x 228mm x 7.0mm
Overall Thickness: 7.0mm
Backing Underlay Thickness: 2.0mm
Surface Finish: Deep Embossed
Wear Layer Thickness: 0.50mm
Qty in box: 5 Planks
M²/sqm in box: 2.052m²
Weight Per Box: 22kg
Boxes per pallet: 55 – 62

WARRANTY

Residential Warranty: 25 years
Commercial Warranty: 15 years

ENGINEERED HYBRID FLOORING COLOUR SELECTION

NATURAL OAK
XQ-SPC-01

FRENCH OAK
XQ-SPC-02

BROWN OAK
XQ-SPC-03

GREY HAZE
XQ-SPC-04

NORDIC WOOD
XQ-SPC-05

HAMPTON
XQ-SPC-06

TECHNICAL DATA

Category	Standard	Result
Size	ISO24342	1800mm x 228mm
Thickness	ISO24346	7.0mm
Wear Layer		0.50mm (Commercial Grade)
Surface Treatment		PU/UV Coating
Surface Finish		Deep Embossed
Box Quantity		5 Planks / 2.052m²
Weight Per Box		22kg
Warranty	Residential	25 years (wear)
	Commercial	15 years (wear)
Colour fastness to light	ISO 105-B02	≥6
	ASTM F1515-15	<7
Abrasion Resistance	ASTM D3884	Pass
Flexibility	ASTM F2199	Pass
Dimensional Stability	EN 434 / ISO 23999	≤0.02%
	ASTM F2199	Pass
Castor Chair	EN 425 / ISO 4918	Pass
Residual Indentation	EN 433 / ISO 24343-1	≤0.1mm
	ASTM F1914-17	<10%
Slip Resistance	AS/NZS 4586:2013 Appendix D	R10
	AS/NZS 4586:2013 Appendix A	P4
Reaction to fire	AS/NZS ISO 9239.1-2003	CRF: 8.0KW/M² Smoke Value: 150% min
TVOC	ASTM D5116-2010	Pass
Formaldehyde Emission Factor	EN 717-1:2004 / ASTM D5116-2010	Pass (24 Hr - μg.m²h = <0.05)
Static Coefficient of Friction	ASTM D2047-11	Pass
	EN 13893	Pass
Chemical Resistance	EN 423 / ASTM F925	No Change/Pass
Electrical Resistance	EN 1081	Pass
Recyling		Suitable

Mocha Oak XQ-LL-01

EXTREME RANGE

Our **Loose Lay Flooring** is an incredibly unique product with stunning natural timber colours and designs. It was revolutionary when it first appeared in the residential and commercial market and has transformed our flooring industry in Australia. Our Loose Lay Flooring has the toughness to withstand high traffic and is 100% waterproof allowing it to be used in all areas together with a natural and authentic timber look. We have specifically designed our boards wider to make any area appear more spacious and have carefully chosen colours and designs that are contemporary.

Our Loose Lay Flooring enables you to redecorate your area in a contemporary style, with the durability to last a lifetime.

FEATURES

- Hard Wearing
- Waterproof
- Natural timber appearance
- Easy to replace boards
- Easy to clean
- Quiet and comfortable to walk on
- Pet Friendly
- Handles well against scratches and scuff marks
- Impact resistance
- Dimensionally stable
- Fire retardant
- Anti-Bacterial Surface Properties
- Stain Resistant properties
- Slip Resistance Class: P4

PRODUCT DETAILS

Dimension: 1219.2mm x 228.6mm x 5.0mm
Overall Thickness: 5.0mm
Surface Finish: Semi Embossed
Wear Layer Thickness: 0.70mm
Qty in box: 8 Planks
M²/sqm in box: 2.23m²
Weight Per Box: 20KG
Boxes per pallet: 50 – 55

WARRANTY

Residential Warranty: 25 years
Commercial Warranty: 15 years

LOOSE LAY FLOORING COLOUR SELECTION

MOCHA OAK
XQ-LL-01

AMERICAN OAK
XQ-LL-02

TASMANIAN OAK
XQ-LL-03

NATURAL GREY
XQ-LL-04

TECHNICAL DATA

Category	Standard	Result
Size	ISO24342	1219.2mm x 228.6mm
Thickness	ISO24346	5.0mm
Wear Layer		0.70mm (Commercial Grade)
Surface Treatment		PU/UV Coating
Surface Finish		Semi Wild
Box Quantity		8 Planks / 2.23m²
Weight Per Box		20kg
Warranty	Residential	25 years (wear)
	Commercial	15 years (wear)
Colour fastness to light	ISO 105-B02	≥7
	ASTM F1515-15	<7
Abrasion Resistance	ASTM D3884	Pass
Flexibility	ASTM F2199	Pass
Dimensional Stability	EN 434 / ISO 23999	≤0.10%
	ASTM F2199	Pass
Castor Chair	EN 425 / ISO 4918	Pass
Residual Indentation	EN 433 / ISO 24343-1	≤0.1mm
	ASTM F1914-17	<10%
Slip Resistance	AS/NZS 4586:2013 Appendix D	R10
	AS/NZS 4586:2013 Appendix A	P4
Reaction to fire	AS/NZS ISO 9239.1-2003	CRF: 8.5KW/M²
TVOC	ASTM D5116-2010	Smoke Value: 145% min
Formaldehyde Emission Factor	EN 717-1:2004 / ASTM D5116-2010	Pass Pass (24 Hr - μg.m²h = <1.3)
Static Coefficient of Friction	ASTM D2047-11	Pass
	EN 13893	Pass
Chemical Resistance	EN 423 / ASTM F925	No Change/Pass
Electrical Resistance	EN 1081	Pass
Recyling		Suitable

Coastal Wood XQ-SPCG-03

EXTRA RANGE

Our **Hybrid Glue Down Flooring**, extra Range is designed and created to suite those who need to enhance the appearance of their space with an affordable, effective and elegant floor. Our Hybrid Glue Down Flooring differentiates from the traditional vinyl planks as it is made up of a limestone and PVC structure to replicate the Hybrid Engineered Flooring. This is made to produce a superior Glue Down Board that is far more dimensionally stable then vinyl planks whilst appearing to look more natural than ever before.

Our Hybrid Glue Down Flooring offers a great solution for both the residential and commercial market as it is durable, economical and retains an authentically beautiful timber appearance.

Like all our flooring ranges our Hybrid Glue Down boards are designed wider than the traditional standard size to make any area appear larger whilst retaining a modern presence.

FEATURES

- Hard Wearing
- Waterproof
- Natural timber appearance
- Quiet and comfortable to walk on
- Easy to clean
- Pet Friendly
- Handles well against scratches and scuff marks
- Impact resistance
- Dimensionally stable
- Fire retardant
- Anti-Bacterial Surface Properties
- Stain Resistant properties
- Slip Resistance Class: P4

PRODUCT DETAILS

Dimension: 1220mm x 228mm x 2.50mm
Overall Thickness: 2.50mm
Surface Finish: Deep Embossed
Wear Layer Thickness: 0.50mm
Qty in box: 14 Planks
M²/sqm in box: 3.894m²
Weight Per Box: 19.8kg
Boxes per pallet: 55 – 60

WARRANTY

Residential Warranty: 20 years
Commercial Warranty: 10 years

HYBRID GLUE DOWN FLOORING COLOUR SELECTION

GREY ASH- XQ
SPCG-01

NATURAL OAK
XQ-SPCG-02

COASTAL WOOD
XQ-SPCG-03

TECHNICAL DATA

Category	Standard	Result
Size	ISO24342	1220mm x 228mm
Thickness	ISO24346	2.50mm
Wear Layer		0.50mm (Commercial Grade)
Surface Treatment		PU/UV Coating
Surface Finish		Deep Embossed
Box Quantity		14 Planks / 3.894m²
Weight Per Box		19.8kg
Warranty	Residential	20 years (wear)
	Commercial	10 years (wear)
Colour fastness to light	ISO 105-B02	≥6
	ASTM F1515-15	<7
Abrasion Resistance	ASTM D3884	Pass
Flexibility	ASTM F2199	Pass
Dimensional Stability	EN 434 / ISO 23999	≤0.02%
	ASTM F2199	Pass
Castor Chair	EN 425 / ISO 4918	Pass
Residual Indentation	EN 433 / ISO 24343-1	≤0.1mm
	ASTM F1914-17	<10%
Slip Resistance	AS/NZS 4586:2013 Appendix D	R10
	AS/NZS 4586:2013 Appendix A	P4
Reaction to fire	AS/NZS ISO 9239.1-2003	CRF: 8.0KW/M²
TVOC	ASTM D5116-2010	Smoke Value: 150% min
Formaldehyde Emission Factor	EN 717-1:2004 / ASTM D5116-2010	Pass Pass (24 Hr - μg.m²h =<0.05)
Static Coefficient of Friction	ASTM D2047-11	Pass
	EN 13893	Pass
Chemical Resistance	EN 423 / ASTM F925	No Change/Pass
Electrical Resistance	EN 1081	Pass
Recyling		Suitable

EXCEL RANGE

Our **Hybrid Glue Down Flooring**, excel Range is designed and created to suite those who need to enhance the appearance of their space with an affordable, effective and elegant floor. The minor difference from the Extra Range is the overall thickness of the boards. Our Hybrid Glue Down Flooring differentiates from the traditional vinyl planks as it is made up of a limestone and PVC structure to replicate the Hybrid Engineered Flooring. This is made to produce a superior Glue Down Board that is far more dimensionally stable then vinyl planks whilst appearing to look more natural than ever before.

Our Hybrid Glue Down Flooring offers a great solution for both the residential and commercial market as it is durable, economical and retains an authentically beautiful timber appearance.

Like all our flooring ranges our Hybrid Glue Down boards are designed wider than the traditional standard size to make any area appear larger whilst retaining a modern presence.

FEATURES

- Hard Wearing
- Waterproof
- Natural timber appearance
- Quiet and comfortable to walk on
- Easy to clean
- Pet Friendly
- Handles well against scratches and scuff marks
- Impact resistance
- Dimensionally stable
- Fire retardant
- Anti-Bacterial Surface Properties
- Stain Resistant properties

PRODUCT DETAILS

Dimension: 1220mm x 180mm x 2.0mm
Overall Thickness: 2.0mm
Surface Finish: Deep Embossed
Wear Layer Thickness: 0.20mm
Qty in box: 20 Planks
M²/sqm in box: 4.392m²
Weight Per Box: 19.5kg
Boxes per pallet: 55 – 60

WARRANTY

Residential Warranty: 10 years

Sandy Oak XQ-SPCG-05

HYBRID GLUE DOWN FLOORING COLOUR SELECTION

NATIVE GREY
XQ-SPCG-04

SANDY OAK
XQ-SPCG-05

DRIFTWOOD
XQ-SPCG-06

TECHNICAL DATA

Category	Standard	Result
Size	ISO24342	1220mm x 180mm
Thickness	ISO24346	2.0mm
Wear Layer		0.20mm (Domestic Grade)
Surface Treatment		PU/UV Coating
Surface Finish		Deep Embossed
Box Quantity		20 Planks / 4.392m²
Weight Per Box		19.5kg
Warranty	Residential	10 years (wear)
Colour fastness to light	ISO 105-B02	≥6
	ASTM F1515-15	<7
Abrasion Resistance	ASTM D3884	Pass
Flexibility	ASTM F2199	Pass
Dimensional Stability	EN 434 / ISO 23999	≤0.02%
	ASTM F2199	Pass
Castor Chair	EN 425 / ISO 4918	Pass
Residual Indentation	EN 433 / ISO 24343-1	≤0.1mm
	ASTM F1914-17	<10%
Slip Resistance	AS/NZS 4586:2013 Appendix D	R9
	AS/NZS 4586:2013 Appendix A	P3
Reaction to fire	AS/NZS ISO 9239.1-2003	CRF: 8.0KW/M²
TVOC	ASTM D5116-2010	Smoke Value: 150% min
Formaldehyde Emission Factor	EN 717-1:2004 / ASTM D5116-2010	Pass Pass (24 Hr - μg.m²h = <0.05)
Static Coefficient of Friction	ASTM D2047-11	Pass
	EN 13893	Pass
Chemical Resistance	EN 423 / ASTM F925	No Change/Pass
Electrical Resistance	EN 1081	Pass
Recyling		Suitable

ABOUT US

XQ Floors is a flooring manufacturer and wholesaler in Australia, delivering high grade timber inspired composite flooring and excellent customer service with a dependable reputation in the industry.

At XQ Floors our products are of high quality, innovative to the latest market trends with meticulously selected design options at an affordable and competitive price to suite all our consumers Australia wide.

We aim to deliver our products with great care and focus on maintaining and sustaining relationships with our consumers.

XQ Floor's founder Frank Alper has had many years of experience in the flooring manufacturing and wholesaling sector. With his experience, dedication and passion for the products he aims to only deliver the best quality timber inspired composite flooring, with styles and colours to meet all consumers requirements.

Working proficiently with manufacturers internationally, he always aspires to design and develop the latest market trends in flooring products, with modern and sophisticated designs and colours suitable to the Australian market. This means the hard work is done from the beginning to make your decision easy as possible when it comes to selecting the right floor for you.

Our selected timber inspired composite flooring range comprises of Engineered Hybrid Flooring, Hybrid Glue Down and Loose Lay Flooring. These are all engineered to replicate a natural timber hardwood appearance, with the benefits of being 100% waterproof and versatile to be used both residentially and commercially because of its hard wearing properties.

Our team at XQ Floors are highly experienced and dedicated in providing you with all the information you need to know about our selected products. Together with our service and experience we will endeavour to guide you in selecting the right flooring option, design and colour to suite your brief.

CONTACT US

Email: sales@xqfloors.com.au
Phone: (03) 8512 0685
Address: 30/830-850 Princes Hwy, Springvale VIC 3171
Website: www.xqfloors.com.au

Images displayed in this brochure may not replicate the exact colour and design.