

Engineered Hybrid ECO Technical Data

Category	Standard	Result
Size	ISO24342	640mm x 128mm
Thickness	ISO24346	7.0mm
Wear Layer		0.50mm (Commercial Grade)
Surface Treatment		PU/UV Coating
Surface Finish		Deep Embossed
Box Quantity		14 Planks / 1.1469m ²
Weight Per Box		12kg
Warranty	Residential	25 years (wear)
	Commercial	15 years (wear)
Colour fastness to light	ISO 105-B02	≥6
	ASTM F1515-15	<7
Abrasion Resistance	ASTM D3884	Pass
Flexibility	ASTM F2199	Pass
Dimensional Stability	EN 434 / ISO 23999	≤0.02%
	ASTM F2199	Pass
Castor Chair	EN 425 / ISO 4918	Pass
Residual Indentation	EN 433 / ISO 24343-1	≤0.1mm
	ASTM F1914-17	<10%
Slip Resistance	AS/NZS 4586:2013 Appendix D	R9, R10
	AS/NZS 4586:2013 Appendix A	P3, P4
Reaction to fire	AS/NZS ISO 9239.1-2003	≥11.0KW/M ²
		Smoke Value: 176 %.min
TVOC	ASTM D5116-2010	Pass
Formaldehyde Emission Factor	EN 717-1:2004 / ASTM D5116-2010	Pass (24 Hr - µg.m ² h = <0.05)
Static Coefficient of Friction	ASTM D2047-11	Pass
	EN 13893	Pass
Chemical Resistance	EN 423 / ASTM F925	No Change/Pass
Electrical Resistance	EN 1081	Pass
Recycling		Suitable

Disclaimer: All information provided on the Technical Data sheet has been provided to the best of our knowledge.

It may be subject to change and may not reflect the exact product purchased as there can be slight variances during production.

If you require any further information in relation to this data sheet, please contact our office.

Contact Information:

Visit: www.xqfloors.com.au

Email: info@xqfloors.com.au

Address: 30/830 - 850 Princes Hwy, Springvale Vic 3170