

Commercial Carpet Tile Technical Data

| Category | Standard | Result |
|-----------------------------|-----------------------------|---------------------------------------|
| Tile Size | ISO24342/EN 994 | 500mm x 500mm |
| Total Thickness | ISO24346/ISO 1765 | 6.5mm - 7.0mm |
| Product Construction Type | | Tuft Multi-Level Loop |
| | | Tuft Level Loop |
| Pile Height | ISO 1766 | 3.5mm - 4.0mm |
| Surface Pile Weight | ISO 8543 | 550 g/m ² (gsm ± 5%) |
| Pile/Colour Material | | 100% Solution Dyed Nylon |
| Backing Construction | | PVC Reinforced Fibre Glass |
| Box Quantity | | 20 Tiles / 5m ² |
| Weight Per Box | | 25kg |
| Limited Warranty | Residential | 10 years |
| | Commercial | 10 years |
| Colour fastness to light | ISO 105-B02 | Pass |
| | ASTM F1515-15 | Pass |
| Castor Chair | ISO 4918 | Pass |
| Flexibility | ASTM F2199 | Pass |
| Dimensional Stability | EN 434 / EN 986 / ISO 23999 | ≤0.1% |
| | ASTM F2199 | Pass |
| Reaction to fire | AS/NZS ISO 9239.1-2003 | CHF: 5.4KW/M ² |
| | | Smoke Value: 117% min |
| Indoor Air Emissions / TVOC | ASTM D5116-2010 / EN 16516 | ≤0.5 mg/m ³ or less (Pass) |
| Electrical Resistance | EN 1081 | Pass |

Disclaimer: All information provided on the Technical Data sheet has been provided to the best of our knowledge.

It may be subject to change and may not reflect the exact product purchased as there can be slight variances during production.

If you require any further information in relation to this data sheet, please contact our office.

Contact Information:

Visit: www.xqfloors.com.au

Email: info@xqfloors.com.au

Address: 30/830 - 850 Princes Hwy, Springvale Vic 3170